Ø1002 **[2] 004** 

WED 13:42 FAX 1 541 664 6384 **ELEVATION CERTIFICATE** 

CITY OF CP

O.M.B. No. 3067-0077 Expires July 31, 1999

## FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to prode elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine he proper Insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR), You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions for completing this form can be found on the following pages, SECTION A PROPERTY INFORMATION FOR INSURANCE COMPANY USE POLICY NUMBER BUILDING OWNER'S NAME lemple ADDRESS (Including Apt., Unit, Sujte anglor Bidg, Number) OR P.O. ROUTE AND BOX NUMBER COMPANY NAIC NUMBER OTHER DESCRIPTION (Lot and Block Numbers, etc.) CITY SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See Instructions): 3. SUFFIX 6. BASE FLOOD ELEVATION (In AO Zumes, use depth) 4. DATE OF FIRM INDEX S. FIRM ZONE 1. COMMUNITY NUMBER 2. PANEL NUMBER Jan 19, 1982 410092 0001 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 XOther (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: Land Land feet NGVD (or other FIRM datum-see Section B, Item 7). SECTION C BUILDING ELEVATION INFORMATION . Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject, building's reference level \_\_\_\_\_. 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 11247. @ feet NGVD (or other FIRM datum-see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of \_\_\_\_\_\_ feet NGVD (or other FIRM datum-see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is ...... feet above ..... or below (check one) the highest grade adjacent to the building. one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? 

Yes 

No 

Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: 

NGVD '29 

Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section 8, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: X Yes No. (See Instructions on Page 4) 5. The reference level elevation is based on: 

actual construction 

construction drawings

(NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required ance construction is complete.) 6. The elevation of the lowest grade immediately adjacent to the building is: 11246 teet NGVD (or other FIRM datum-see Section B. Item 7). SECTION D COMMUNITY INFORMATION 1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor as defined by the ordinance is: [ ] [ ] feet NGVD (or other FIRM datum-see Section B, Item,7). 2. Date of the start of construction or substantial improvement May 4, 1998 E317 mated

PHONE

04/08/98 WED 13:43 FAX 1 541 664 6384

CITY OF CP

## SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation formation when the elevation information for Zones A1—A30, AE, AH, A (with BFE),V1—V30,VE, and V (with BFE) is required, community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifler is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the

CERTIFIER'S NAME

LICENSE NUMBER (or Affix Seat)

TITLE


COMPANY NAME

C

Copies should be made of this Certificate for: 1) community official, 2) Insurance agent/company, and 3) building owner.

comments: Elevation datum based on Firm Reference Mark
BM2 - fee Surveyors Topog attacked to drawings-

Elevations hereon are based on Bench Mark RM2, a brassdisk set on top of the south westerly headwall of a box culvert at Highway 99 and Griffen Creek as established by aerial Mapping



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.